Resistance table

BUSCHJOST Solenoid Valves

Which materials for which fluids?

The resistance table supports you in your search for suitable materials and compiles information on the chemical resistance of sealing and enclosure materials for gaseous and liquid media. **The table is subject to updating.

Contents of the resistance table

- The suitability of the materials is confirmed by a simple "+".
- For some media, only the minimum requirement is confirmed with a "+". This means that higher quality materials can also be used.
- Ask if you are unsure, even if a medium is not listed.
- Operating conditions cannot be derived from the table.
- There is no such thing as an unconditional application. Therefore, also consider operational dependencies such as pressure, temperature, viscosity, concentration, degree of contamination. These can have a negative effect on the longevity of the valve.
- The table does not claim to be complete.
- No warranty claims can be derived from the information given.
- We reserve the right to change the information given at any time without notice.

Technical hotline Germany +49 5731 18660 99

			Material Sealing																							Material Housing																			
Media	Density (kg/m³)	Gaseous	-30°C 140°C EPDM	-30°C 140°C EPDM/EPDM	-30°C 120°C EPDM/PTFE	-15°C 200°C FFKM	-10°C 140°C FKM	-10°C 140°C FKM/FKM	-40°C 300°C Metall	-40°C 80°C Metall/HP	-20°C 400°C Metall/Wills®	-10°C 80°C NBR	-10°C 80°C NBR/NBR	-200°C 80°C PCTFE	-40°C 250°C PEEK-HT	-40°C 80°C Peek/PCTFE	-196°C 140°C PEEK/PCTFE-HP	PEEK/UHMW-PE	-10°C 90°C POM	-196°C 230°C PTFE	-10°C 200°C PTFE/FKM	-10°C 80°C PTFE/Peek	40°C 230°C PTFE/Silikon	-196°C 250°C AISI 304 - 1.4301	-196°C 300°C AISI 316 - 1.4408	-196°C 300°C AISI 316 TI - 1.4571(81)	-196°C 80°C AISI 316L - 1.4404	-40°C 250°C AISI 316L - 1.4435	-40°C 250°C AISI 318LN - 1.4462	-40°C 80°C AISI 5165M - 1.4418	aluminium AL anodised	-40°C 200°C CC499K red brass	-196°C 300°C CW617N brass	-10°C 300°C EN-GJL250 grey cast	-20°C 300°C EN-GP240GH cast steel	-10°C 300°C EN-JS1025 ductile iron	-10°C 300°C P250GH+N - C22.8 PN160	PTFE Polyetrafluoroethylene	PVC	Polyvinyl chloride
potassium hydroxide KOH, 50%, aqueous	1000		+		+															+				+	+	+																	
2-methylpentan, isohexane, liquid																				+				+	+	+							+									
Acetone CH3COCH3	791		+														+			+				+		+			+			+	+	+	+							
Acetylene C2H2	1.17	ja	+									+					+			+				+		+			+			+	+	+	+							
Additives for Fuels							+	+												+	+			+	+	+							+									
Air	1.2	ja	+	+	+		+	+				+					+		+	+	+		+	+	+	+			+		+	+	+	+	+	+	+					+
Ammoniac NH3	0.77	ja	+		+												+			+				+	+	+							+									
Antifrogen N	1140																			+													+									
Argon Ar	1.78	ja					+					+					+			+				+	+	+			+			+	+		+							
Argon, liquified cryogenic -186°C														+			+			+				+		+	+						+									
Bilge Water (water-oil mix)	1000		+				+					+								+	+					+							+	+	+							
Biodiesel, Rapsmethylester (RME)	885						+	+												+				+	+	+							+									
biogas (wet, max. 3% H2S)		ja					+																		+																		
Biogas <= 0,5% H2S		ja					+					+					+			+	+			+		+			+					+		+							
Boron Trichloride BCL3 <0,5% Halogen																																													
Brake Fluid	1100		+	+				+												+					+	+						+	+		+							
Butadien C4H6	2.4	ja																		+					+	+																	
Calibration gas, test gas, dry	0.72	ja					+										+			+				+					+														

| | | | Material Sealing | | | | | | | | | | | | | | | | | | | | | Material Housing | | | | | | | | | | | | | | | | | | |

| | | | Material Sealing | | | | | | | | | | | | | | | | | | | | | Material Housing | | | | | | | | | | | | | | | | | | |

			Material Sealing																					Material Housing																							
Media	Density (kg/m³)	Gaseous	-30°C 140°C EPDM	-30°C 140°C EPDM/EPDM	-30°C 120°C EPDM/PTFE	-15°C 200°C FFKM	-10°C 140°C FKM	-10°C 140°C FKM/FKM	-40°C 300°C Metall	-40°C 80°C Metall/HP	-20°C 400°C Metall/Wills®	-10°C 80°C NBR	-10°C 80°C NBR/NBR	-200°C 80°C PCTFE	-40°C 250°C PEEK/HT	-40°C 80°C Peek/PCTFE	-196°C 140°C PEEK/PCTFE-HP	PEEK/UHMW-PE	-10°C 90°C POM	-196°C 230°C PTFE	-10°C 200°C PTFE/FKM	-10°C 80°C PTFE/Peek	-40°C 230°C PTFE/Silikon	-196°C 250°C AISI 304 - 1.4301	-196°C 300°C AISI 316 - 1.4408	-196°C 300°C AISI 316 Ti - 1.4571(81)	-196°C 80°C AISI 316L - 1.4404	-40°C 250°C AISI 316L - 1.4435	-40°C 250°C AISI 318LN - 1.4462	-40°C 80°C AISI S165M - 1.4418	aluminium AL anodised	-40°C 200°C CC499K red brass	-196°C 300°C CW617N brass	-10°C 300°C EN-GJL250 grey cast	-20°C 300°C EN-GP240GH cast steel	-10°C 300°C EN-JS1025 ductile iron	-10°C 300°C P250GH+N - C22.8 PN160	PTFE Polytetrafluoroethylene	PVC	Polyvinyl chloride
Nitric acid aqueous 40%, HNO3	1100						+													+	+				+	+														+		
Nitrogen dioxide NO2	2.053																			+				+	+	+																
Nitrogen Gas N2	1.25	ja	+				+	+		+		+					+		+	+	+			+		+		+		+	+	+	+	+							
Nitrogen oxides, nitrous gases NOx		ja															+			+				+	+	+																
Nitrous Oxide N2O	2	ja					+			+							+			+	+			+		+	+			+				+								
Odorant		ja				+											+			+				+		+				+												
Oxygen Liquid, -183°C LOX	1140																			+						+																
Oxygen O2	1.43	ja					+	+									+			+	+			+	+	+				+			+	+	+	+	+				
paint, ink - highly viscous			+				+					+									+					+		+		+				+								
Phenol, Carbolic Acid - diluted with water						+														+					+	+																
Propane/Butane gaseous C3H8	2	ja					+					+					+			+	+			+	+	+			+			+	+	+	+	+				
Propionic acid C3H6O2	990						+													+	+			+	+	+																
propylene glycol C3H8O2							+					+								+													+	+	+							
Propylene, Propene - C3H6	1.915	ja					+													+				+	+	+							+	+							
Rape Oil							+	+												+						+							+	+	+	+					
refrigerant R290, R600a																				+				+	+	+							+	+							
Refrigerant R407C	2.51	ja																		+				+	+	+							+	+							
Resins							+													+	+			+	+	+																
sea water	1000											+																					+								
sewage gas, proportionally H2S, NH3	0.77	ja	+																							+																
silan gas	1.34	ja					+													+	+			+	+	+																
slurry of chalk							+																	+										+								
Sodium hydroxide (sodium hydroxide), NaOH, 30%, +20°C			+																	+					+	+																
sodium hypochlorite NaOCl (Chlorine bleach) max. 12%, +20°C																	+			+						+																

| | | | Material Sealing | | | | | | | | | | | | | | | | | | | | | Material Housing | | | | | | | | | | | | | | | | | | |

| | | | Material Sealing | | | | | | | | | | | | | | | | | | | | | Material Housing | | | | | | | | | | | | | | | | | | |